

# Wire Rope Slings



Eye & Eye



Eye & Thimble

Sliding Choker



Eye & Eye



Eye & Thimble









Eye & Hook



Thimble & Hook



Thimble & Thimble

					Minimum Sling Length	Standard Eye Size (in) WxL	Thimble Eye Size (in) WxL	Eye Hook Cap. (tons)	Sliding Choker Hook (in)
 <b>6x19</b>	1/4	0.65	0.48	1.3	1' 6"	2x4	7/8x1-5/8	1	3/8
	5/16	1.0	0.74	2.0	1' 9"	2-1/2x5	1-1/16x1-7/8	1	3/8
	3/8	1.4	1.1	2.9	2' 0"	3x6	1-1/8x2-1/8	1 1/2	3/8
	7/16	1.9	1.4	3.9	2' 3"	3-1/2x7	1-1/4x 2-1/4	2	1/2
	1/2	2.5	1.9	5.1	2' 6"	4x8	1-1/2x 2-3/4	3	1/2
	9/16	3.2	2.4	6.4	2' 9"	4-1/2x9	1-1/2x2-3/4	5	5/8
	5/8	3.9	2.9	7.8	3' 0"	5x10	1-3/4x3-1/4	5	5/8
	3/4	5.6	4.1	11	3' 6"	6x12	2x3-1/4	7	3/4
	7/8	7.6	5.6	15	4' 0"	7x14	2-1/4x4-1/4	11	7/8
	1	9.8	7.2	20	4' 6"	8x16	2-1/2x 4-1/2	11	1
 <b>6x37</b>	1-1/8	12	9.1	24	5' 0"	9x18	2 7/8x5-1/8	15	1-1/8
	1-1/4	15	11	30	5' 6"	10x20	3-1/2x6-1/2	15	1-1/4
	1-3/8	18	13	36	6' 0"	11x22	3-1/2x6-1/4	22	1-3/8
	1-1/2	21	16	42	7' 0"	12x24	3-1/2x6-1/4	22	1-1/2
	1-3/4	28	21	57	8' 0"	14x28	4-1/2x9	30	
	2	37	28	73	9' 0"	16x32	6x12	37	
	2-1/4	44	35	89	10' 0"	18x36	7x14	45	
2-1/2	54	42	103	11' 0"	20x40				

Note: Larger diameter slings available

1. 1 Ton=2,000lbs

2. Minimum sling length when using standard eyes

## WARNING

Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Slings should not be used at angles of less than 30°.